



GENERAL PRODUCT SHEET

TAMPlug – Permanent Bridge Plug System

PRODUCT DESCRIPTION:

The TAMPlug Permanent Bridge Plug System utilizes a modular design valve sub that can quickly adapt to work with a full complement of TAM element types and sizes. This flexibility enables faster job preparation and timely deployment to the field for a variety of solutions.

PROVIDE SOLUTIONS FOR:

- Open or cased hole zonal isolation
- Permanent bridge plug for abandonments
- Lost circulation zones in harsh environments
- Cement base for sidetracking

FEATURES:

- Pressure balanced element during run in well
- Utilizes field proven TAMCAP valving
- Modular design allows for a variety of elements to be used depending on application
- Integral circulation/fill ports built into the valve sub

BENEFITS:

- Very robust design and shorter overall length enhances deployment in short radius trajectories
- Work string can be set to run dry or set to auto-fill to adapt to different fluids and solids content in the well
- Right-Hand release sub built into the tool
- Vertical or horizontal wells

TOOL SIZES:

4.25 in. OD Setting Head Element Options

Element OD		Element Type	Top Connection
in.	mm		(in.)
4.25	108	IE	2.88 EU
4.25	108	SE	2.88 EU
4.25	108	VE	2.88 EU
5.06	129	IE	2.88 EU
5.25	133	SE	2.88 EU
5.25	133	VE	2.88 EU
5.50	140	VE	2.88 EU
6.19	157	IE	2.88 EU
7.00	178	IE	2.88 EU
7.38	187	VE	2.88 EU

5.06 in. OD Setting Head Element Options

Element OD		Element Type	Top Connection
in.	mm		(in.)
5.06	129	IE	3.50 IF
5.06	129	IE	3.50 IF
5.25	133	SE	3.50 IF
5.25	133	VE	3.50 IF
5.50	140	IE	3.50 IF
5.50	140	SE	3.50 IF
5.50	140	VE	3.50 IF
7.00	178	IE	3.50 IF
7.38	187	VE	3.50 IF
11.00	279	IE	3.50 IF
11.00	279	VE	3.50 IF
14.56	370	IE	3.50 IF
14.56	370	VE	3.50 IF

